

Product

The WeR@Home[™] Hub is an intelligent, home control panel for managing and communicating with the on-site WeR@Home[™] peripherals. The Hub is the central gateway that connects to the mobile app and to the WeR@Home[™] Servers. Features include:

- User remote control and management access to the system, via the cloud, using smartphones, tablets, and PCs
- User interface software available for iOS™ and Android™ operating systems and Windows®-based browsers
- Optional built-in 3G/4G(HSPA+) modem with automatic APN setting and support for 850/900/1800/1900 MHz bands
- Support of up to 64 security peripherals, 24 safety peripherals and up to 32 users, including two master users
- Home automation functionality from the Z-Wave[®] network can be integrated with WeR@Home[™] by connecting the Z-Wave[®] Plus Extender
- Support of automatic over-the-air software programming and configuration upgrade (RSU)
- Accessories included:
 - o Rechargeable backup battery
 - o Ethernet LAN cable
 - o Universal power adapter/charger

WeR@Home[™] Smart Living

The WeR@Home[™] suite allows living life fully through smart connected homes

- Home security and safety at the core
- Notifications of security events and remote management of the home in real time
- Modular and expandable manage connected home devices with Z-Wave[®] expansion
- Smart Rule engine for automation decide which device, condition, or event will trigger which actions and at what time
- Live HD video anytime, on any screen
- Save energy and money by ensuring that lights and air conditioning are turned off when not at home





anytime on any screen

WeR@Home[™]



Datasheet

Hub

ES8000CP Home Management Hub

Specifications

COMMUNICATIONS

- Maximum RF range: 600 m (1,968 ft.) open air
- Maximum transmission: 25 mW (14 dBm)
- Proprietary bi-directional radio protocol
- Modulation and frequency: DSSS, 2.4 GHz
- Data security: 128 bit AES encryption
- Cloud (internet):
 - LAN/ethernet port: downlink 384 kBps, uplink 120 kBps
 Optional 3G/4G (HSPA+) support (separate PN)

POWER

- 100-240 V AC to 5 V DC power adapter/charger
- 3.7 V 1.4 Ah Li-polymer rechargeable backup battery (up to 3 hours)

DIMENSIONS

- Size (H x W x D): 141 x 75 x 41 mm (5.6 x 3 x 1.6 in.)
- Weight: 125 g (0.28 lb.) + 35 g (0.08 lb.) backup battery

ENVIRONMENT

- Storage ambient temperature range: -20°C to 60°C (-4°F to 140°F)
- Operating ambient temperature range with battery: -5°C to 50°C (23°F to 122°F)
- **RF operating humidity:** Up to 95% non-condensing

COMPLIANCE

- FCC: cellular/non-cellular version YXG-ES8000GP/Y4I- ES8000CP
- IC: cellular version 11061A-ES8000GP



ESUG05068 Rev. 2.3 For more information, go to: http://www.essence-grp.com/smart-living/wer-at-home